


UNAUTHORIZED USE OF THIS
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
3890	A	PRE-RELEASE	DG	8-12
5181	B	SEE DAR	DG	9-14



NOTES:

- CONNECTOR TYPE J1, 2, 3: TYPE 'SMA' FEMALE
- RoHS COMPLIANT.

ELECTRICAL SPECIFICATIONS

FREQUENCY:	100 - 500 MHz.
INSERTION LOSS:	< 0.45 dB
VSWR:	< 1.25:1
PHASE BALANCE:	±5°
AMPLITUDE BALANCE:	±0.2 dB
POWER:	200 WATT
ISOLATION:	>18 dB

MATERIAL AL. ALLOY 6061-T651	DWN S.Cornell	DATE 8-31-12	Innovative Power Products		
	ENG DG	DATE 8-12			
FINISH CHEM FILM, CLEAR, PER MIL-DTL-5541, TYPE 2, REV. F, CLASS 3 (ROHS COMPLIANT)	MANUF	DATE	TITLE OUTLINE		
	CAGE CODE: 437R2		2 - WAY 100 - 500 MHz 200 WATT		
TOLERANCE .XX ±.02 .XXX ±.010 ANG. ±1/2°	SHEET 1 OF 1	SCALE 1:1	SIZE B	P/N IPP-1210	REV. B