


UNAUTHORIZED USE OF THIS
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
1191	A	INITIAL RELEASE	TJD	9-06
1208	B	REVISE SPECIFICATIONS	TJD	10-06
1403	C	POWER RATING WAS 200 WATTS	TJD	2-08
1453	D	REVISED SPECIFICATIONS	DG	5-08
4673	E	SEE DAR	DG	11-13



ELECTRICAL SPECIFICATIONS

FREQUENCY:	200 - 1000 MHz.
INSERTION LOSS:	< 0.50 dB
VSWR:	< 1.30:1
ISOLATION:	> 16 dB
AMPLITUDE BALANCE:	±0.75 dB
PHASE BALANCE:	±5°
POWER:	150 WATT
TEMPERATURE:	-55°C TO 85°C

- NOTES:**
- LEAD MATERIAL: 99.99% PURE SILVER .005 [.127] THICK.
 - SEE 90° APPLICATION NOTE FOR FURTHER INFORMATION.
 - RoHS COMPLIANT.
 - DATA AND SPECIFICATIONS APPLY WHEN PART IS MOUNTED IN IPP TEST FIXTURE TF-1012. TEST FIXTURE CONFIGURATION/FOOTPRINT AVAILABLE ON REQUEST.

PORT CONFIGURATION				
INPUT	J1	J2	J3	J4
J1	---	ISOLATION	-3dB<0 DEG	-3dB<-90 DEG
J2	ISOLATION	---	-3dB<-90 DEG	-3dB<0 DEG
J3	-3dB<0 DEG	-3dB<-90 DEG	---	ISOLATION
J4	-3dB<-90 DEG	-3dB<0 DEG	ISOLATION	---

MATERIAL AL. ALLOY, 6061-T6	DWN	DG	DATE	9-06					
	ENG	TJD	DATE	9-06					
FINISH CHEM FILM CLEAR PER MIL-DTL-5541, TYPE 2, REV F, CLASS 3 ROHS COMPLIANT	MANUF	TP	DATE	9-06					
	CAGE CODE: 437R2								
TOLERANCE .XX ±.02 [.50] .XXX ±.005 [.127] ANG. ±1/2°	SHEET	OF	SCALE	2:1	SIZE	P/N	IPP-2057	REV.	E
	1	1			B				

TITLE
OUTLINE, COUP., 90°, 200-1000 MHz. 150W