


UNAUTHORIZED USE OF THIS
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
2561	E	SEE DAR	TJD	6-10
3516	F	SEE DAR	DG	2-12
5813	G	SEE DAR	DG	9-15




NOTES:

1. LEAD MATERIAL: 99.99% PURE SILVER, .040 [1.016] WIDE x .005 [.127] THICK x .150 [3.810] MIN. LONG.
2. SUBSTRATE MATERIAL: BeO COVER MATERIAL: EPOXY
3. FLANGE MATERIAL: COPPER PLATING: NICKEL
4. LEAD(S) WELDED TO SUBSTRATE.
5. RoHS COMPLIANT.

ELECTRICAL SPECIFICATIONS

INPUT POWER: 100 WATT
FREQ: DC - 6.0 GHZ.
VSWR: 1.10:1 DC - 4.2 GHZ.
1.25:1 DC - 6 GHZ.

POWER DERATING CURVE



PART NO.	VALUE	TOLERANCE
IPP-TB220-50	50 OHMS	+/- 5%

MATERIAL	[2] [3]	DWN	DG	DATE	6-07	</	
----------	-------------	-----	----	------	------	--	--