



UNAUTHORIZED USE OF THIS
DRAWING IS STRICTLY PROHIBITED

DAR	REV	DESCRIPTION	APPVD	DATE
7709	A	INITIAL RELEASE	DG	6-19
7822	B	SEE DAR	DG	8-19
8091	C	SEE DAR	DG	3-20


ELECTRICAL SPECIFICATIONS

PART NO.	VALUE	INPUT POWER	FREQUENCY	VSWR
IPP-TN111-50	50 OHMS ±5%	150 WATT	DC-3.0 GHz	<1.25:1 @ 2.0 GHz <1.30:1 @ 3.0 GHz



NOTES:

1. LEAD MATERIAL: 99.99% PURE SILVER, .050 [1.270] WIDE x .005 [.127] THICK x .250 [6.350] MIN. LONG.
2. LEAD FINISH: GOLD PLATE PER MIL-G-45204, TYPE 3, GRADE A, 20 MICRO-INCHES MAX.
3. SUBSTRATE MATERIAL: AIN
4. LEAD(S) WELDED TO SUBSTRATE.
5. THICK FILM.
6. RoHS COMPLIANT.
7. BACKSIDE METALIZATION: THICK FILM PALLADIUM SILVER.



MATERIAL SEE NOTES	DWN S.Cornell	DATE 2-7-19	Innovative Power Products		
FINISH SEE NOTES	ENG DG	DATE 2-19			
TOLERANCE IN [MM] .XX ±.02 [.50] .XXX ±.010 [.254]	CAGE CODE: 437R2		TITLE TERMINATION, AIN, 150 WATT, FLANGELESS		
	SHEET OF 1 1	SCALE 4:1	SIZE B	P/N IPP-TN111-XXX	REV. C